

LJ Series Line Matrix Printers

Designed for HP® Systems!



- Up to 1800 lines per minute (lpm)!
- 100% HP® LineJet series compatible.
- HP® Web JetAdmin compatible.
- Virtually unlimited duty cycle.
- Complies with industry standards for open systems printing.
- Handles paper and multi-part forms with ease.
- Flexible connectivity and interfacing.
- Enclosed cabinet models for quiet operation in office environments.
- Pedestal models for fast, easy access and operation in harsh, shop-floor environments.
- QMS Code V™ & PGL compatibility at no additional charge.

Unbeatable HP® Compatibility.

Designed for HP® compatibility, the TallyGenicom LJ Series of line matrix printers offer superior performance, reliability and quality for mission-critical applications. As the price/performance leaders in line printers, the LJ Series costs less to buy, less to service and less to use while setting new throughput and functionality milestones.

Fast, Quality Printing

The LJ Series builds on the reputation of our 6300 and T6200 Standard Series printers, adding plug-in compatibility with HP systems. The LJ Series offers the same advanced set of features found in the 6300 and T6200 Standard Series: Auto Gap, Auto Form Profiling, SmartRibbon, extensive connectivity options, compatibility with wide range of host systems.

SmartRibbon Technology.

The patented TallyGenicom SmartRibbon™ ensures a uniformly high contrast over the ribbon's life – the last form looks as good as the first (not available with 6306LJ).

Complies With Industry Standards For Open Systems.

For true open systems printing with workstations, mainframes and PC applications, the LJ series supports a variety of printing languages and protocols including HP® LineJet® (Enhanced HP PCL II & PJI), HP LP Series, HP256X, HP235X, IBM® Proprinter® and Epson®, and more.

Available Configuration:

- 6306LJ** Line matrix printer at 600 LPM, Serial and Parallel, Open Pedestal, 55 dBA
- 6306LJ** Line matrix printer at 600 LPM, Serial and Parallel, Enclosed Pedestal, 52 dBA
- 6312LJ** Line matrix printer at 1200 LPM, Serial, Parallel & Ethernet, Open Pedestal, 60 dBA
- 6312LJ** Line matrix printer at 1200 LPM, Serial, Parallel & Ethernet, Enclosed Pedestal, 56 dBA
- T6212LJ** Line matrix printer at 1200 LPM, Enclosed Cabinet, Serial + Parallel + Ethernet
- T6215LJ** Line matrix printer at 1500 LPM, Enclosed Cabinet, Serial + Parallel + Ethernet
- T6218LJ** Line matrix printer at 1800 LPM, Enclosed Cabinet, Serial + Parallel + Ethernet

Print Speed	6306LJ 600 LPM, 6312LJ 1200 LPM, T6212LJ 1200 LPM, T6215LJ 1500 LPM, T6218LJ 1800 IPM
Graphic Speed	6306LJ 75 IPM, 6312LJ 150 IPM, T6212LJ 150 IPM, T6215LJ 187 IPM, T6218LJ 225 IPM
Print Method	Line impact dot matrix
Resolution	240 x 288 (HxV)
Character Density	5, 6, 6.7, 7.5, 8.3, 8.6, 10, 12, 13.3, 15, 16.7, 17.1, 20
Line Density	1.5, 2, 3, 4, 5, 6, 8, 9, 10, 12 (plus variable line spacing)
Character Sets	Over 1000 Character Sets including PCL II sets
Character Styles	Bold, italic, superscript, subscript, underline, overline, strike through
Standard Connectivity	RS-232 Serial (up to 38.4K baud), IEEE 1284 Parallel, Ethernet 10BaseT / 100 BaseT (Optional for 6306LJ); all ports hot
Optional Connectivity	Ethernet 10BaseT / 100 BaseT for 6306LJ
Standard Emulation	HP® LineJet® (Enhanced HP PCL II & PJI), HP LP Series, HP256X, HP235X, Epson® FX-1180, IBM® Proprinter III XL, Printronix® P Series; Graphics: Tally® Industrial Graphics; QMS® CODE V™ Version 2; Printronix® PGL
Print Monitor	Tally WebPanel: Virtual Control Panel from any Web Browser; Email notification of job completion/error status; HP® Web JetAdmin compatibility (discovery, configuration, printer status)
Fonts	Draft, Data Processing, Courier, Gothic, OCR A & B; Barcodes: Code 39, Code 128, Interleaved 2 of 5, UPC-A, UPC-E, EAN 8, EAN 13, EAN 128, Codabar, MSI, PDF-417, POSTNET
Consumables	40, 60, 250 million (only 40 for 6306LJ)
STD Paper Handling	Straight through paper path, paper out and paper motion detection, forms position retained in non-volatile memory; Auto-Gap on 6306LJ and 6312LJ
Number of Copies	Up to 6-part forms
Form Thickness	.025" maximum
Paper Drive	Straight through paper path
Paper Type	Continuous paper
Paper Weight	15-100 lb.
Paper Size	Width 3" - 18.7"; Length: 1 - 255 lines
Printable Area	Up to 13.6"
Physical Weight	6306LJ, 6312LJ Pedestal Models 214 lbs.; T6218LJ Pedestal Model 212 lbs.; T6212LJ, T6215LJ Cabinet Models: 185 lbs.
PhysicalSize	Pedestal Models: 28.3" x 39.7" x 23.4"; Cabinet Models: 40"x28.2"x28.3"
Power Voltage	90-130 / 180-264 V
Power Frequency	50/60 Hz (auto-ranging)
Compliance	Energy Star compliant, Ozone-free, RoHS, Microsoft, ISO-compliant, Meditech Approved
Workload	175,000 - 512,000 PPM
Reliability MTBF	16,000 hours @ 25% duty cycle, 25% page density
Drivers	Windows 2003 Server, XP, 2000, NT 4.0, 95/98
Temperature	10°C to 40°C (operating); -40°C to 66°C (non-operating)
Humidity	10% to 90% non-condensing (operating); 5% to 95% non-condensing (non-operating)
Acoustic	6306LJ 52 dBA, 6312LJ 56 dBA, T6212LJ 50 dBA, T6215LJ 52 dBA, T6218LJ 55 dBA
Warranty	1-year Limited On-Site (First 90 days parts, labor, travel; Remainder of year: Parts only)
Option 1	Ethernet 10BaseT / 100 BaseT for 6306LJ



© 2009 Printronix, Inc. All rights reserved. Genicom, Tally, TallyGenicom, TG TallyGenicom, the TG Logo, Intellifilter, Intelliprint and Intellipress are trademarks or registered trademarks of Printronix, Inc. Microsoft, Windows, and the Windows logo are trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries. All other trademarks, product names, company names or logos herein are the property of their respective owners. Product appearance and/or specifications are subject to change without notice.

Printed Date: 16/05/2009

PRINTRONIX®

GLOBAL PRINTING...ENABLED.

14600 Myford Road
Irvine, CA 92606
800-665-6210
www.tallygenicom.com