

9022 Monochrome



Faster print to first page

The 9022 monochrome laser printer represents the latest in affordable printing solutions for desktop and small workgroups. With excellent resolution and quick first page out times, the 9022 is the perfect choice for producing attractive documents quickly and precisely.

Print speeds of up to 22 pages per minute and a peak duty cycle of 30,000 pages per month makes the 9022 an excellent choice for anyone in need of a fast and reliable monochrome laser printer. In addition to rapid operation, the light weight and small footprint mean that the 9022 can be placed wherever printing requirements dictate.

In order to meet the various needs of IT administrators and business professionals, the 9022 can be configured for many different connectivity requirements including wireless (802.11b), Ethernet, Parallel and High Speed USB (2.0).

Taken together, the speed, size and connectivity qualities of the 9022 mean that this latest monochrome laser from TallyGenicom is certain to fulfill the business printing needs of even the most demanding organizations

Key Features

- Print speed up to 22 pages per minute
- Less than ten-second first page out time.
- Compact design allows for easy deployment
- True 1200 dpi print resolution
- Workloads up to 30,000 pages per month
- Excellent cost of operation
- Parallel and Hi-Speed USB standard, 10/100 Ethernet Optional
- Standard 16 MB memory
- Robust 166 MHz Processor for rapid document creation
- Auto Run CD provides easy installation

Consumables

Mobile Printers

Laser Printers

Line Matrix Printers

Serial Matrix Printers

9022 Monochrome

Laser Printers

Features & Specifications

Print Technology	Electrophotographic laser																		
Print Speed (pages per minute)	22 pages per minute																		
Time to First Page	Less than 10 seconds																		
Warm-up Time	Less than 40 seconds																		
Graphic Resolution	1200 x 1200 dpi																		
Processor	Samsung SPGPm 166 MHz																		
Memory (MB) - Std/Max	16 MB / 144 MB																		
Emulations	Standard: PCL 6 / 5e , Epson, IBM Proprinter Optional: PostScript Level 3																		
Fonts	1 Bit Map and 45 scaleable, 136 PS3 fonts (optional)																		
Interfaces	Standard: Parallel (IEEE 1284), Hi-Speed USB (Version 2.0) Optional: Internal Ethernet (10Base-T/100Base-T), Wireless LAN (802.11b)																		
Interface Intelligence	Automatic Interface Switching																		
Printer Drivers	Windows 9.x / NT4.0 / ME / 2000 / XP, 2003, Mac OS X																		
Paper Handling	<table border="0"> <tr> <td><i>Paper Sizes</i></td> <td>MPT: Letter, A4, A5, A6, Legal, Folio, Officio, Executive, ISO B5, JIS B5, 3"x5", Std Cassette - Letter, A4, A5, Legal, Executive, Folio, Officio, SO B5, JIS B5, 3"x5" Opt Cassette: Letter, A4, A5, Legal, Executive, Folio, Officio, ISO B5, JIS B5, 3"x5"</td> </tr> <tr> <td><i>Envelope Sizes</i></td> <td>MPT only: Monarch, No.9, No.10, DL, C5</td> </tr> <tr> <td><i>Paper Types</i></td> <td>MPT: paper, transparencies, labels, heavy paper stock, envelopes Standard Cassette: paper Optional Cassette: paper</td> </tr> <tr> <td><i>Paper Weight</i></td> <td>Cassette: 16-24 lbs; MPT: 16-60 lbs Cover</td> </tr> <tr> <td><i>Non-printable area</i></td> <td>0.15" from each edge / envelopes - 0.59" from left and 10mm from all other sides</td> </tr> <tr> <td><i>Duplexing</i></td> <td>Manual</td> </tr> <tr> <td><i>Std Input Capacity</i></td> <td>Manual feed, 50-sheet multi-purpose tray (MPT) + 250-sheet universal cassette</td> </tr> <tr> <td><i>Opt Input Capacity</i></td> <td>2nd universal cassette accepts 250 sheets</td> </tr> <tr> <td><i>Std Output Capacity</i></td> <td>150-sheet face down</td> </tr> </table>	<i>Paper Sizes</i>	MPT: Letter, A4, A5, A6, Legal, Folio, Officio, Executive, ISO B5, JIS B5, 3"x5", Std Cassette - Letter, A4, A5, Legal, Executive, Folio, Officio, SO B5, JIS B5, 3"x5" Opt Cassette: Letter, A4, A5, Legal, Executive, Folio, Officio, ISO B5, JIS B5, 3"x5"	<i>Envelope Sizes</i>	MPT only: Monarch, No.9, No.10, DL, C5	<i>Paper Types</i>	MPT: paper, transparencies, labels, heavy paper stock, envelopes Standard Cassette: paper Optional Cassette: paper	<i>Paper Weight</i>	Cassette: 16-24 lbs; MPT: 16-60 lbs Cover	<i>Non-printable area</i>	0.15" from each edge / envelopes - 0.59" from left and 10mm from all other sides	<i>Duplexing</i>	Manual	<i>Std Input Capacity</i>	Manual feed, 50-sheet multi-purpose tray (MPT) + 250-sheet universal cassette	<i>Opt Input Capacity</i>	2nd universal cassette accepts 250 sheets	<i>Std Output Capacity</i>	150-sheet face down
<i>Paper Sizes</i>	MPT: Letter, A4, A5, A6, Legal, Folio, Officio, Executive, ISO B5, JIS B5, 3"x5", Std Cassette - Letter, A4, A5, Legal, Executive, Folio, Officio, SO B5, JIS B5, 3"x5" Opt Cassette: Letter, A4, A5, Legal, Executive, Folio, Officio, ISO B5, JIS B5, 3"x5"																		
<i>Envelope Sizes</i>	MPT only: Monarch, No.9, No.10, DL, C5																		
<i>Paper Types</i>	MPT: paper, transparencies, labels, heavy paper stock, envelopes Standard Cassette: paper Optional Cassette: paper																		
<i>Paper Weight</i>	Cassette: 16-24 lbs; MPT: 16-60 lbs Cover																		
<i>Non-printable area</i>	0.15" from each edge / envelopes - 0.59" from left and 10mm from all other sides																		
<i>Duplexing</i>	Manual																		
<i>Std Input Capacity</i>	Manual feed, 50-sheet multi-purpose tray (MPT) + 250-sheet universal cassette																		
<i>Opt Input Capacity</i>	2nd universal cassette accepts 250 sheets																		
<i>Std Output Capacity</i>	150-sheet face down																		
Toner Capacity (5% page coverage)	Replacement process unit - 5,000 pages*, Initial toners supplied are up to 3,500 pages*																		
Acoustic Level (ISO 7779)	Printing - 51 dB(A); Standby - 39 dB(A); Sleep Mode - Background level																		
Duty Cycle (Pages per month)	30,000 Maximum																		
Environmental	<table border="0"> <tr> <td><i>Temperature</i></td> <td>50°F - 89.6°F</td> </tr> <tr> <td><i>Humidity</i></td> <td>10% - 80% relative humidity, non-condensing</td> </tr> </table>	<i>Temperature</i>	50°F - 89.6°F	<i>Humidity</i>	10% - 80% relative humidity, non-condensing														
<i>Temperature</i>	50°F - 89.6°F																		
<i>Humidity</i>	10% - 80% relative humidity, non-condensing																		
Physical (HxWxD)	10.94" x 14.1" x 17.8"; Weight: 22.04 lbs including consumables																		
Power Requirements	120 V, 50/60 Hz																		
Power Consumption	Energy Star Compliant, Average in printing: 400W, Sleep Mode: 15W																		
Options	2nd cassette (250-sheet), SIMM with PostScript 3 & PCL Barcodes, 128MB Memory Internal Ethernet (10Base-T/100Base-T), Wireless LAN (802.11b)																		
Warranty	One Year, return to depot																		



9022 with Optional Universal Cassette

*Based on 5% coverage of Letter page

Tally, GENICOM and TallyGenicom are registered trademarks of TallyGenicom, L.P. All other company and product names are trademarks or registered trademarks of their respective owner. Specifications are subject to change without notice.

Copyright © 2005 TallyGenicom, L.P.



4500 Daly Drive, Suite 100
Chantilly, VA 20151

T 800.436.4266
www.tallygenicom.com