

9025 Monochrome



The most powerful tool in your office

The 9025 Monochrome Laser Printer from TallyGenicom provides workgroup level performance for the business environment at an extremely affordable price. High duty cycle, exceptional paper handling options and a wide range of functions make the 9025 an exceptional value and a leader in its class.

Printing at 25 pages per minute, combined with PostScript Level 3 functionality, standard duplexing and optional wireless print capability, means that the 9025 can serve as a robust platform for the business printing needs of workgroups.

Configuring the 9025 printer with an internal secure wireless network card provides the opportunity to bring printing to anywhere you can send a wireless signal – no more problems with “network drops”.

All of these functionalities, combined with the exceptional service and support that you have come to expect, make the TallyGenicom 9025 an excellent workgroup printing option.

Proven Performance

- 25 ppm print speed
- High duty cycle of 150,000 per month
- Fast response – less than 12 seconds to first page
- Low cost of operation provides excellent printing value
- 1200 dpi quality printing

High Speed and Excellent Network Capabilities

- 266 MHz, 32 Bit RISC architecture processor delivers blazing speed
- Available network connectivity
- Wireless option provides freedom of movement for rapid deployment in non-networked environments
- Network printer manager provides easy set-up, configuration and administration

Exceptional Paper Handling

- Standard duplexing increases productivity
- Standard 550-sheet paper cassette and 100-sheet multifunction tray
- Handles Standard, Letter, Legal, Executive and many other paper formats
- Low jam rate means fewer user interventions

Consumables

Ink Jet Printers

Laser Printers

Line Matrix Printers

Serial Matrix Printers

Features & Specifications

Print Technology	Electrophotographic Laser																		
Print Speed	Up to 25 pages per minute																		
Time to First Page	Less than 12 seconds																		
Graphic Resolution	600 x 600 dpi, 1200 dpi Quality																		
Processor	32 Bit, 266 MHz (RISC)																		
Memory (MB) - Std/Max	32 MB / 160 MB																		
Emulations	Standard: PCL6 / PCL5e Postscript 3, Epson																		
Fonts	1 Bit Map and 45 scaleable, 136 PS3 fonts; Optional: Barcode																		
Interfaces	<table border="0"> <tr> <td><i>Standard</i></td> <td>9025: Parallel, USB (v 2.0) 9025N: Parallel, USB (v 2.0), Ethernet 10/100Base-T 9025W: Internal Ethernet (10Base-T & 100Base-Tx), Wireless LAN (802.11b)</td> </tr> <tr> <td><i>Optional</i></td> <td>Serial</td> </tr> </table>	<i>Standard</i>	9025: Parallel, USB (v 2.0) 9025N: Parallel, USB (v 2.0), Ethernet 10/100Base-T 9025W: Internal Ethernet (10Base-T & 100Base-Tx), Wireless LAN (802.11b)	<i>Optional</i>	Serial														
<i>Standard</i>	9025: Parallel, USB (v 2.0) 9025N: Parallel, USB (v 2.0), Ethernet 10/100Base-T 9025W: Internal Ethernet (10Base-T & 100Base-Tx), Wireless LAN (802.11b)																		
<i>Optional</i>	Serial																		
Emulation Intelligence	Automatic Emulation Sensing																		
Interface Intelligence	Automatic Interface Switching																		
Printer Drivers	Windows 9.x/NT 4.0/2000/XP/MAC/ME, Linux and Unix Posters, N-Up, Booklets, Duplex, Forms, Overlays, Watermarks																		
Network Utilities	SyncThru																		
Paper Handling	<table border="0"> <tr> <td><i>Paper Sizes</i></td> <td>MPF - Letter, Legal, Folio, A5 Executive, Statement, ISO B5, JIS B5, A5, A6, A4 Standard cassette - Letter, Legal, Folio, Executive, ISO B5, JIS B5, A4, A5 Optional cassette - Letter, Legal, Folio Executive, ISO B5, JIS B5, A4, A5 Duplex - Letter, Legal, Folio, A4</td> </tr> <tr> <td><i>Envelope Sizes</i></td> <td>COM 10, Monarch, C5, C6, DL</td> </tr> <tr> <td><i>Paper Types</i></td> <td>MPF - paper, transparencies, labels, heavy paper stock, envelopes Standard cassette - paper Optional cassette - paper</td> </tr> <tr> <td><i>Paper Weight</i></td> <td>Cassette - 16-28 lbs.; MPF - 16-43 lbs.; Duplex - 20-24 lbs.</td> </tr> <tr> <td><i>Non-printable area</i></td> <td>Paper - 0.16" from each side; Envelopes - 0.4" from all sides</td> </tr> <tr> <td><i>Duplexing</i></td> <td>Standard</td> </tr> <tr> <td><i>Std Input Capacity</i></td> <td>Manual feed, 100-sheet Multi-Purpose Feeder (MPF) plus 500-sheet universal cassette</td> </tr> <tr> <td><i>Opt Input Capacity</i></td> <td>2nd universal cassette accepts 500 sheets</td> </tr> <tr> <td><i>Std Output Capacity</i></td> <td>250-sheet face down; 100-sheet face up</td> </tr> </table>	<i>Paper Sizes</i>	MPF - Letter, Legal, Folio, A5 Executive, Statement, ISO B5, JIS B5, A5, A6, A4 Standard cassette - Letter, Legal, Folio, Executive, ISO B5, JIS B5, A4, A5 Optional cassette - Letter, Legal, Folio Executive, ISO B5, JIS B5, A4, A5 Duplex - Letter, Legal, Folio, A4	<i>Envelope Sizes</i>	COM 10, Monarch, C5, C6, DL	<i>Paper Types</i>	MPF - paper, transparencies, labels, heavy paper stock, envelopes Standard cassette - paper Optional cassette - paper	<i>Paper Weight</i>	Cassette - 16-28 lbs.; MPF - 16-43 lbs.; Duplex - 20-24 lbs.	<i>Non-printable area</i>	Paper - 0.16" from each side; Envelopes - 0.4" from all sides	<i>Duplexing</i>	Standard	<i>Std Input Capacity</i>	Manual feed, 100-sheet Multi-Purpose Feeder (MPF) plus 500-sheet universal cassette	<i>Opt Input Capacity</i>	2nd universal cassette accepts 500 sheets	<i>Std Output Capacity</i>	250-sheet face down; 100-sheet face up
<i>Paper Sizes</i>	MPF - Letter, Legal, Folio, A5 Executive, Statement, ISO B5, JIS B5, A5, A6, A4 Standard cassette - Letter, Legal, Folio, Executive, ISO B5, JIS B5, A4, A5 Optional cassette - Letter, Legal, Folio Executive, ISO B5, JIS B5, A4, A5 Duplex - Letter, Legal, Folio, A4																		
<i>Envelope Sizes</i>	COM 10, Monarch, C5, C6, DL																		
<i>Paper Types</i>	MPF - paper, transparencies, labels, heavy paper stock, envelopes Standard cassette - paper Optional cassette - paper																		
<i>Paper Weight</i>	Cassette - 16-28 lbs.; MPF - 16-43 lbs.; Duplex - 20-24 lbs.																		
<i>Non-printable area</i>	Paper - 0.16" from each side; Envelopes - 0.4" from all sides																		
<i>Duplexing</i>	Standard																		
<i>Std Input Capacity</i>	Manual feed, 100-sheet Multi-Purpose Feeder (MPF) plus 500-sheet universal cassette																		
<i>Opt Input Capacity</i>	2nd universal cassette accepts 500 sheets																		
<i>Std Output Capacity</i>	250-sheet face down; 100-sheet face up																		
Toner (Based on 5% coverage of letter paper)	Replacement process unit - 10,000 pages																		
Acoustic Level	Printing - 53 dB(A); Standby - 35 dB(A); Sleepmode - Background Level																		
Duty Cycle (Pages per month)	150,000 pages per month (typical use)																		
Physical (HxWxD)	15.2 x 17.6 x 12.8 inches																		
Weight	<33.1 lbs. including consumables																		
Environmental	<table border="0"> <tr> <td><i>Temperature</i></td> <td>50°F - 89°F</td> </tr> <tr> <td><i>Humidity</i></td> <td>20% - 80% relative humidity, non-condensing</td> </tr> </table>	<i>Temperature</i>	50°F - 89°F	<i>Humidity</i>	20% - 80% relative humidity, non-condensing														
<i>Temperature</i>	50°F - 89°F																		
<i>Humidity</i>	20% - 80% relative humidity, non-condensing																		
Power Requirements	(100V/120V Models) 90-140 VAC, 50/60 Hz, 3%																		
Operating Altitude	8,200 feet (maximum)																		
Power Consumption	Energy Star Compliant, Less than 12 watts in sleep mode, Standby 100 watts (maximum), Less than 350 watts printing (average)																		
Options	2nd cassette (500-sheet), 16/32/64/128 MB Memory, Internal Ethernet (10Base-T & 100Base-T), Wireless LAN 802.11b, Serial Interface, Barcode Emulation																		
Warranty	One year return to depot																		



9025 with manual feeder tray



9025 with optional second paper tray



NB: Paper is a highly variable medium, and should be tested prior to purchase. The quoted consumable life is the average for the printer when used under normal operating conditions.

Tally, GENICOM and TallyGenicom are registered trademarks of TallyGenicom, L.P. All other company and product names are trademarks or registered trademarks of their respective owner. Specifications are subject to change without notice.

Copyright © 2004 TallyGenicom, L.P.



4500 Daly Drive, Suite 100
Chantilly, VA 20151

T 800.436.4266
www.tallygenicom.com