

MIP360/360i Vehicle Printer

New!

MIP360i, with Norand/Intermec 6820 compatibility. ****Three year warranty included with this model****



Key Features

- ✓ Rugged Construction
- ✓ Easy paper loading
- ✓ Simple to change ribbon
- ✓ Can handle fan-fold or single sheet
- ✓ Print speeds up to 432 cps
- ✓ Bluetooth or 802.11 connectivity, RS-232 Serial and Parallel also available

Consumables

Mobile Printers

Laser Printers

Line Matrix Printers

Serial Matrix Printers

High speed, easy to use vehicle printer

Ideally suited to route delivery and other Mobile Applications.

Getting the Job Done on Time

Printing at up to 432 characters per second, delivery information is provided quickly, allowing you to move to the next location as fast as possible.

In Vehicle Ease of Use - Paper Loading

Paper loading is done without opening covers, and paper stabilizer guides provide a solid backing for easy location.

In Vehicle Ease of Use - Ribbon Changing

The MIP360 uses a long life 2 mil character ribbon - in typical usage, this means you only have to change ribbons once every three or four months.

In Vehicle Ease of Use - Forms Flexibility

The MIP360 can handle up to four part continuous forms - it can also print on single top glued forms giving you flexibility for future requirements.

Excellent Print Quality

The 24-wire print head produces clear, crisp output of texts and graphics. There's support for IBM® Proprinter® X24e and Epson® ESC/P2 emulations. A variety of resident typefaces ensure fast, high-quality text.

Print Configuration Control

Users can choose either of two configurations, which are accessible through the control panel or application programs. To reduce the risk of accidental job interruption, the printer's control panel can be locked out under program control.

Optional Accessories

Ruggedized brackets, paper input trays and vehicle power cords designed for the MIP360 are available. Custom hardware can be designed for your fleet if desired

MIP360/360i Vehicle Printer

Mobile Printers

Features & Specifications

Printing Technology	Serial Impact Dot Matrix		
Print Method	Bi-directional, logic-seeking		
Print Speed (cps)		10 cpi	12 cpi
	LQ	113	135
	NLQ	225	270
	Draft	360	432
Print Head	24-wire; 0.0079" (0.20 mm) dia.		
Fonts	Draft, Courier, Sans Serif, Script, Prestige, Orator, OCR-A/B, Roman		
Printing	Character Spacing: 10,12,15,17.1,18, and 20 cpi; LF Interval: 60 ms per line at 6 lpi; Print Line: 8.0 in. Dot Graphics (dpi): 120 to 360H x 180 to 360V		
Paper Handling	Features: Paper parking, automatic fanfold positioning for zero tear-off		
	Paper Drive: Push tractors (rear feed) with special tractor platforms for quick paper loading; friction-feed platen for cut sheet		
	Paper Dimensions:		
	Continuous Forms Width	4-10.5 in. (102-267mm)	
	Continuous Forms Length	4 in. or more (102mm)	
	Cut Sheet Width	4-10.5 in. (102-267 mm)	
	Cut Sheet Length	3-14.3 in. (76-364 mm)	
	Paper Type: 1 to 4-part side-glued or paper stapled fan fold continuous forms		
	Number of Copies: 4 (original + 3 copies)		
	Maximum Forms Thickness: Up to 0.014 in. (0.35 mm); Paper Slew: 5.6 ips		
Emulations	IBM® ProPrinter XL24e, Epson® ESC/P2, Norand/Intermec 6820 compatibility		
Interfaces & Connectivity	Bluetooth and RS-232; Wireless Ethernet 802.11b and RS-232; Centronics parallel and RS-232; Connectors: 36 pin Parallel; DB25F Serial		
Physical Specifications	Size (HxWxD): 12.25 x 17.5 x 6.5 in. (311.0 x 444.5 x 166.6mm)		
	Weight: 17.7 lbs (8.0 kg)		
Operating Environment	Voltage: 12/24 VDC Nominal (10.5-28 VDC); 100/240 VAC to 12 VDC power converter optional		
	Temperature: Operating: -4° to 140° F (-20° to 60° C) DC; -4° to 113° F (-20° to 45° C) AC; Storage: -22° to 158° F (-30° to 70° C)		
	Humidity: 10% to 85% relative (no condensation)		
Reliability	MTBF: 15,000 hours @ 5% duty cycle Ribbon Life: Black: Up to 2 million characters		
Regulatory Compliance	UL 1950, CSA C22.2/950, Class B of FCC Part 15B.CE marking, EMC Immunity: IEC 61000-4-2 level 3 (Direct 4kV, Air 8kV), Automotive Standards: IEC 60068, ASTM 999		
Warranty	MIP360: One year return to depot MIP360i: Three year return to depot		



Connectivity

- > Bluetooth and RS-232 or
- > 802.11x and RS-232 or
- > Parallel and RS-232

Power

- > 12/24 VDC Printer
- > 110/240 VAC Adapter to 12 VDC



4500 Daly Drive, Suite 100
Chantilly, VA 20151

T 800.436.4266
www.tallygenicom.com