

MIP3P / MIP3T / MIP3F

Durable, easy to use mobile printers

Ideally suited to route delivery and other mobile applications



MIP3P

MIP3P Portable Printer

Battery-operated tractor-feed printer with shoulder strap – portable printing where you need it, in your vehicle, on foot or at a customer site. Internal paper storage protects media, and provides ready to go printing.



MIP3T

MIP3T Fixed Mount Tractor Feed Printer

For in-vehicle use, this compact printer can be mounted in a variety of locations, making it suitable for use in any truck or van, where continuous 1- to 4-part form printing is required.



MIP3F

MIP3F Fixed Mount Friction Feed Printer

For in-vehicle use, this compact printer can also be mounted in a variety of locations. Its compact size makes it suitable for use in law enforcement and other mobile applications where single sheet or individual multi-part forms are used.

Easy Ribbon Changing

The 2 Million character cassette utilizes a reinker to achieve a compact size and provides consistent print quality throughout its life. A precision ribbon shield makes loading easy, quick and convenient.

Easy Paper Loading

To make paper loading fast and simple, the print mechanisms used in the MIP3X tractor feed printers is moved out of the way during paper loading, providing direct access to the tractors. Paper loading in the MIP3F friction feed unit is made simple by use of a paper guide where the form is easily slid into its print position.

Options and Accessories

Ruggedized brackets and vehicle power cords are available, as well as 110/220v to 12v power converters for in office/warehouse use, and battery charging for the portable printer.

Consumables

Mobile Printers

Laser Printers

Line Matrix Printers

Serial Matrix Printers

Features & Specifications

Printing Technology	Serial Impact Dot Matrix
Print Method	Bi-directional , logic seeking
Print Speed	288 cps @ 12 cpi
Print Head	9-wire
Fonts	Pica, Elite, Proportional, Prestige, Quadro, Brougham, Gothic
Printing	Character Spacing: 10, 12, 15, 17 cpi
Paper Handling	Features: Open mechanism for easy paper loading on tractor units; insertion slot for friction drive unit Paper Dimensions: Continuous Forms Width 3-9.5 in. (76-241mm); 3-8.5 (76-216mm) for MIP3F Continuous Forms Length 4 in. or more (102mm) Number of Copies Original plus three copies, max. forms thickness: 0.014"
Emulations	IBM® ProPrinter with Key Epson Commands
Interfaces & Connectivity	Bluetooth and RS-232; Wireless Ethernet 802.11b and RS-232, USB and RS-232; Centronics parallel and RS-232
Physical Specifications (HxWxD)	MIP3T: Dimensions 4.46" x 15" x 4.3"; Weight: 5.5 lbs MIP3F: Dimensions 5.4 x 15" x 4.3"; Weight: 5.3 lbs (2.4 kg) MIP3P: Dimensions 12" x 15" x 4.3"; Weight 9.5 lbs (4.3 kg)
Operating Environment	Voltage: 12/24 VDC Nominal, 10.5 - 30 VDC; 110/220 VAC converter available Temperature: Operating: 14° to 104° F (-10° to 40° C); Storage: -22° to 158° F (-30° to 70° C)
Regulatory Compliance	Class A of FCC Part 15B
Warranty	One year return to depot



MIP3P Portable Printer